



Network

Dome

## XND-6010

2M H.265 Dome Camera



### Key Features

- Built-in 2.4mm fixed lens
- Max. 60fps@all resolutions (H.265/H.264)
- Day & Night (ICR), WDR(150dB)
- Loitering, Directional detection, Fog detection
- Digital auto tracking, Sound classification, Heatmap
- People counting, Queue management, Tampering
- Motion detection, Handover
- Dual SD slots (Max. 512GB)
- Hallway view, WiseStream II support, IK08

### Compatible Devices



SPB-IND11



SBP-300CM



SBP-120WM



SBP-300PM



SBP-300KM



SBP-300WM1



SBP-300LM



SBP-390WM2



SBP-300WM



SBP-300B



SBP-300HM7



SBP-300NB

## XND-6010

2M H.265 Dome Camera



### Specifications

| Video                         |                       |                                                                                                                   |
|-------------------------------|-----------------------|-------------------------------------------------------------------------------------------------------------------|
| Imaging Device                | Size                  | 1/2.8"                                                                                                            |
|                               | Type                  | CMOS                                                                                                              |
| Resolution                    |                       | 1920x1080, 1280x1024, 1280x960, 1280x720, 1024x768, 800x600, 800x448, 720x576, 720x480, 640x480, 640x360, 320x240 |
| Max. Framerate                | H.265/H.264           | 60fps/50fps(60Hz/50Hz)                                                                                            |
|                               | MJPEG                 | 30fps                                                                                                             |
| Min. Illumination (Lux)       | Color(1/30sec, 30IRE) | 0.055                                                                                                             |
|                               | BW(1/30sec, 30IRE)    | 0.0055                                                                                                            |
| Video Out                     |                       | CVBS: 1.0 Vp-p / 75Ω composite for installation,<br>USB: Micro USB Type B                                         |
| Lens                          |                       |                                                                                                                   |
| Focal Length (mm)             |                       | 2.4                                                                                                               |
| Max Aperture Ratio (F number) | Wide                  | 2.0                                                                                                               |
| Angular Field of View         | Horizontal            | 139°                                                                                                              |
|                               | Vertical              | 73°                                                                                                               |
|                               | Diagonal              | 167°                                                                                                              |
| Min. Object Distance          |                       | 0.4m(1.31ft)                                                                                                      |
| Focus Control                 |                       | Fixed                                                                                                             |
| Pan / Tilt / Rotate           |                       |                                                                                                                   |
| Pan / Tilt / Rotate Range     | Pan                   | 0°~354°                                                                                                           |
|                               | Tilt                  | 0°~67°                                                                                                            |
|                               | Rotate                | 0°~355°                                                                                                           |
| Operational                   |                       |                                                                                                                   |
| Day & Night                   |                       | Auto(ICR)                                                                                                         |
| Backlight Compensation        |                       | BLC, HLC, WDR, SSDR                                                                                               |
| Wide Dynamic Range (dB)       |                       | 150                                                                                                               |
| Digital Noise Reduction       |                       | SSNR V                                                                                                            |

## Operational

|                                          |                |                                                                                                                                                                                             |
|------------------------------------------|----------------|---------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Digital Image Stabilization              |                | Support                                                                                                                                                                                     |
| Defog                                    |                | Support                                                                                                                                                                                     |
| Motion Detection                         | Quantity       | 8ea                                                                                                                                                                                         |
|                                          | Shape          | 8point Polygonal zones                                                                                                                                                                      |
| Privacy Masking                          | Quantity       | 32ea                                                                                                                                                                                        |
|                                          | Shape          | 4point Quadrangle zones                                                                                                                                                                     |
|                                          | Color / Option | Gray, Green, Red, Blue, Black, White, Mosaic                                                                                                                                                |
| Gain Control                             |                | Low, Middle, High                                                                                                                                                                           |
| White Balance                            |                | ATW, AWC, Manual, Indoor, Outdoor                                                                                                                                                           |
| LDC                                      |                | Support                                                                                                                                                                                     |
| Electronic Shutter                       | Mode           | Minimum, Maximum, Anti flicker                                                                                                                                                              |
|                                          | Speed Range    | 2~1/12,000sec                                                                                                                                                                               |
| Video Rotation                           |                | Flip, Mirror, Hallway view(90°/270°)                                                                                                                                                        |
| Alarm Interface                          | In/Out         | Input 1ea, Output 1ea                                                                                                                                                                       |
| Alarm Triggers                           |                | Analytics, Network disconnect, Alarm input                                                                                                                                                  |
| Alarm Events When Alarm Trigger Occurred |                | File upload(image): e-mail/FTP,<br>Notification: e-mail,<br>Recording: SD/SDHC/SDXC or NAS recording at event triggers,Alarm output,<br>Handover: PTZ preset,send message by HTTP/HTTPS/TCP |
| Audio In                                 |                | Selectable(mic in/line in), Built-in mic                                                                                                                                                    |
| Audio Out                                |                | Line out                                                                                                                                                                                    |

## Analytics

|                       |        |                                                                                                                                                                                                                                                  |
|-----------------------|--------|--------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Analytics Events      | Normal | Defocus detection, Motion detection, Tampering, Fog detection, Face detection, Audio detection, Sound classification, Virtual area(Lotering, Intrusion, Enter/Exit, Appear/Disappear), Virtual line(Crossing, Direction) , Digital auto tracking |
| Business Intelligence | Normal | People counting, Queue management, Heatmap                                                                                                                                                                                                       |

## Network

|                   |                    |                                                                                                                               |
|-------------------|--------------------|-------------------------------------------------------------------------------------------------------------------------------|
| Ethernet          |                    | RJ-45(10/100BASE-T)                                                                                                           |
| Video Compression |                    | H.265/H.264: Main/Baseline/High, MJPEG                                                                                        |
| Audio Compression |                    | G.711 u-law /G.726 selectable,G.726(ADPCM) 8kHz,G.711 8kHz,<br>G.726: 16kbps,24kbps,32kbps,40kbps,<br>AAC-LC: 48kbps at 16kHz |
| Smart Codec       |                    | Manual, WiseStream II                                                                                                         |
| Bitrate Control   |                    | H.265/H.264: CBR or VBR,<br>MJPEG: VBR                                                                                        |
| Streaming         | Unicast            | Up to 20 users                                                                                                                |
|                   | Multicast          | Support                                                                                                                       |
|                   | Multiple Streaming | Up to 10 profiles                                                                                                             |

## Network

|                                   |        |                                                                                                                                                                                                                    |
|-----------------------------------|--------|--------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Protocol                          |        | IPv4, IPv6, TCP/IP, UDP/IP, RTP(UDP), RTP(TCP), RTCP, RTSP, NTP, HTTP, HTTPS, SSL/TLS, DHCP, FTP, SMTP, ICMP, IGMP, SNMPv1/v2c/v3(MIB-2), ARP, DNS, DDNS, QoS, UPnP, Bonjour, LLDP, SRTP(TCP, UDP Unicast), PIM-SM |
| Application Programming Interface | ONVIF  | S, G, T                                                                                                                                                                                                            |
|                                   | Others | SUNAPI(HTTP API), Hanwha Vision Open Platform                                                                                                                                                                      |
| Direct Cloud Connection           |        | Optional (needs gateway)                                                                                                                                                                                           |

## Security

|                        |  |                                                                         |
|------------------------|--|-------------------------------------------------------------------------|
| OS / Firmware Protect  |  | Encrypted firmware, Secure boot, Signed firmware                        |
| User authentication    |  | Digest authentication                                                   |
| Network authentication |  | IEEE 802.1X(EAP-TLS, EAP-LEAP)                                          |
| Secure Communication   |  | HTTPS, SRTP                                                             |
| Access Control         |  | IP-based access control                                                 |
| Data Protect           |  | Encryption credentials, Encrypt compress for live recording file export |
| Audit                  |  | Access / System / Event Log management                                  |
| Device ID              |  | Device certificate(Hanwha Vision Root CA)                               |
| Secure Storage         |  | SDcard partition encrypt(AES-256)                                       |

## General

|              |                    |                                 |
|--------------|--------------------|---------------------------------|
| Memory       | RAM                | 1GB                             |
|              | Flash              | 256MB                           |
| Edge Storage | Micro SD/SDHC/SDXC | Max. 256GB x 2slot(Total 512GB) |

## Environmental & Electrical

|                     |             |                                 |
|---------------------|-------------|---------------------------------|
| Operating Condition | Temperature | -10°C~+55°C(+14°F~+131°F)       |
|                     | Humidity    | 0~90% RH(non-condensing)        |
| Storage Condition   | Temperature | -50°C~+60°C(-58°F~+140°F)       |
|                     | Humidity    | 0~90% RH(non-condensing)        |
| Input Voltage       |             | PoE(IEEE802.3af, Class3), 12VDC |
| Power Consumption   | PoE         | Max. 6.5W                       |
|                     | 12VDC       | Max. 6W                         |

## Mechanical

|                    |  |                           |
|--------------------|--|---------------------------|
| Color              |  | Ivory                     |
| Material           |  | PC(Polycarbonate)         |
| Product Dimensions |  | ø110.0x90.0mm(4.33x3.54") |
| Product Weight     |  | 625g(1.38lb)              |

## Certifications & Standards

|             |  |                |
|-------------|--|----------------|
| Environment |  | IEC 62262 IK08 |
|-------------|--|----------------|

**DORI (EN62676-4 standard)**

|                                  |      |                |
|----------------------------------|------|----------------|
| <b>Detect (25PPM/ 8PPF)</b>      | Wide | 14.4m(47.10ft) |
| <b>Observe (63PPM/ 19PPF)</b>    | Wide | 5.7m(18.84ft)  |
| <b>Recognize (125PPM/ 38PPF)</b> | Wide | 2.9m(9.42ft)   |
| <b>Identify (250PPM/ 76PPF)</b>  | Wide | 1.4m(4.7ft)    |

# XND-6010

2M H.265 Dome Camera



**CAD**

Unit: mm [inch]

